



DATA SHEET – Primaseal (Non Fire Rated)

Door:

- **Core:** 38mm Flaxboard – Stiles, rails & head 38x38mm
- **Faces:** 3mm High Density Fibreboard, Primed Finish
- **Lipping:** None.
- **Weight:** Approximately 30kg (based on 2032x813mm door leaf)

Surround Frame:

- **Structure:** Red Deal, rebated. Minimum 70x44mm section with 12mm deep rebate. Butt jointed and screwed.

Dimensions:

- **Door Leaf Sizes:** 2032x864x44mm (80”x34”), 2032x813x44mm (80”x32”), 1981x762x44mm (78”x30”), 1981x711x44mm (78”x28”), 1981x660x44mm (78”x26”), 1981x610x44mm (78”x24”).

On Site Care & Installation

Site Handling and Storage:

Door should be adequately protected from exposure to excessive moisture and splashing by corrosive or staining materials.

The fixing of door assemblies should be left as late in the building programme as possible to avoid damage arising from other operations. Delivery should be planned so as to reduce the storage times on site to the practical minimum.

Where doors or doorsets have to be stored, the building should be dry and well ventilated at a constant temperature. Do not store in damp, freshly plastered, drywall or concrete areas until materials have completely dried.

Door leaves should be stored flat on bearers to keep them away from floor or ground contact. Doors should be stored at least 10ft away from and heat source to prevent uneven drying.