



ESSENTIAL N3000 OAK 44MM FD30 SPECIFICATION FSC

<u>CORE</u>	SOLID CHIPBOARD (36MM) DENSITY 500 kgs/m ³
<u>STILES</u>	SINGLE 38mm SQUARE SOFTWOOD EACH EDGE
<u>RAILS</u>	TWO NUMBER 38MM SOFTWOOD RAILS TO TOP AND BOTTOM OF DOOR
<u>SUBSTRATE</u>	3.2mm MDF
<u>LIPPINGS</u>	6mm (NOMINAL) HARDWOOD TO BOTH VERTICAL EDGES CONCEALED BY FACE VENEER, CLEAR FACTORY LACQUER TO LIPPINGS, LIPPINGS MAY REQUIRE STAINING ON SITE PRIOR TO SEALING AFTER FITTING/SIZING THE DOOR.
<u>FACING</u>	0.6mm ECONOMY GRADE OF AMERICAN WHITE VENEERS, CONTAINING SMALL NATURAL DEFECTS AND VARIED GRAIN, NOT NECESSARILY CENTRE BOOKED MATCHED.
<u>GLAZING</u>	IF REQUIRED AND AS SPECIFIED IN ACCORDANCE WITH TEST CERTIFICATION. MAX 1.2 m ² TOTAL AREA.
<u>FIRE RATING</u>	FD30 (S) WHEN INTUMESCENT SEALS ARE FITTED TO DOOR LEAF OR DOOR FRAME/LINING AS TEST CERTIFICATION (DETAILS ON REQUEST). FITTED 'Q' MARK FIRE PLUG (TRADA) AND ALSO CERTIFIRE LABEL (BWF)
<u>ACOUSTIC</u>	31 db SOUND REDUCTION WITH CORRECT CONFIGURATION OF INTUMESCENT/ACOUSTIC SEAL INCLUDING AT THE THRESHOLD, DETAILS ON REQUEST. (REFER TO LORIENT CATALOGUE, TESTED WITH 15X4MM 'DS' OR 'BATWING' AND LAS8001 DROP SEAL)
<u>FINISH</u>	2 COATS OF MATT U/V ACRYLIC LACQUER TO BOTH FACES AND EDGES
<u>PROTECTION</u>	CARDBOARD ONE SIDE, POLYTHENE WRAPPED
<u>DURABILITY</u>	SEVERE DUTY RATED TO DD171 AND EN1192

THE ABOVE SPECIFICATION IS CURRENT As we are constantly improving our product range, we reserve the right to Make changes without prior notice,